

Model	Go Go® ES 2 <sup>1</sup>
Part Number	S81
Weight Capacity	250 lbs.
Maximum Speed	Up to 4 mph
Ground Clearance <sup>4</sup>	1.5" at motor / 0.75" at anti-tips
Turning Radius <sup>4</sup>	31"
Overall Length <sup>4</sup>	36.75"
Overall Width <sup>4</sup>	19.5"
Seat-to-Ground Height <sup>3</sup>	20"- 21"
Seat-to-Deck Height <sup>3</sup>	16.25"-17.25"
Front Tires	2" x 7.5" solid
Rear Tires	3" x 7.5" solid
Range Per Charge <sup>2,3</sup>	Up to 6.24 miles
Total Weight	With batteries: 77.5 lbs. Without batteries: 58 lbs.
Heaviest Piece When Disassembled <sup>4</sup>	41.4 lbs. (scooter base)
Standard Seating	Type: Foldable, compact, vinyl-covered Weight: 17 lbs. Material: Black vinyl Dimensions: Width: 17" Depth: 15"
Motor Output	24-volt DC motor, sealed mini-transaxle
Battery Requirements <sup>5</sup>	Size: (Two) 12 AH Weight: 9 lbs. each
Battery Charger	Off-board, 2 amp
Color	Black

### HCPCS Code: K0800 (Group 1, Standard)

- <sup>1</sup> Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- <sup>2</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- <sup>3</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- <sup>4</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- <sup>5</sup> Battery weight may vary based on manufacturer.

(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com |    

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

0004952-102722

**GO GO**<sup>®</sup>  
**es 2**<sup>1</sup>

**OUTSTANDING  
VALUE...**

**...EXCEPTIONAL  
DURABILITY**



FDA Class II Medical Device<sup>1</sup>

**LIVE YOUR BEST<sup>®</sup>**

pridemobility.com |    

# OUTSTANDING VALUE...

# ...EXCEPTIONAL DURABILITY

Foldable, compact,  
vinyl-covered  
seating with  
armrests

Modular design  
for easy  
serviceability



Two speed  
settings for  
indoor and  
outdoor use

Removable  
front canvas  
basket

Large, removable front  
canvas basket.

High and low speed settings for  
indoor and outdoor use.

Foldable, compact, vinyl-covered  
seating with armrests.

The Go Go® ES 2 from Pride® combines exceptional value and easy transportation together in a compact, lightweight package. The stylish Go Go ES 2 has a weight capacity of 250 lbs., variable motor speeds and a convenient canvas basket located on the tiller.

## Additional Features

- Lightweight, one-piece frame for added stability and easy portability
- Modular design for easy serviceability

## Color



Black

## Accessories

- Weather cover
- Military patches

