

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy® Passport

Document Information: INFINF3838/Rev F/March 2021

Class of Use	A
Weight Capacity	250 lbs. (113 kg/17 stone 12 lbs.)
Maximum Speed ¹	Up to 3.6 mph (5.8 km/h)
Ground Clearance ²	3 in. (79 mm) at motor
Turning Radius ²	24.25 in. (616 mm)
Overall Size ^{2, 6}	Length: 40 in. (1016 mm) Width: 23.5 in. (597 mm)
Drive Wheels	12 in. (305 mm), pneumatic United States only: 11.25 in. (288 mm), perforated
Caster Wheels	8 in. (203 mm), solid
Anti-tip Wheels	1.75 in. (44 mm)
Suspension	Limited
Range ^{1, 4, 7}	Standard Battery: Pneumatic Tires: Up to 9.6 miles (15 km) at 250 lbs. (113 kg) Up to 11 miles (17.7 km) at 200 lbs. (90 kg) Perforated Tires (United States Only): Up to 7.9 miles (12.7 km) at 250 lbs. (113 kg) Up to 8.6 miles (13.9 km) at 220 lbs (100 kg) Optional Travel Battery: Pneumatic Tires: Up to 5.7 miles (9.2 km) at 250 lbs. (113 kg) Up to 6.3 miles (10.1 km) at 200 lbs. (90kg) Perforated Tires (United States Only): Up to 4.6 miles (7.4 km) at 250 lbs.(113 kg) Up to 5 miles (8 km) at 220 lbs 100 kg)
Component Weights ⁵	Complete Assembly without battery (pneumatic tires): 56.6 lbs. (25.6 kg) Complete Assembly without battery (perforated tires, United States only): 59.8 lbs. (27.2 kg) Standard Battery: 7.6 lbs. (3.4 kg) Optional Travel Battery: 5.2 lbs. (2.4 kg)
Drivetrain	Two motor, rear-wheel drive
Brakes	"Intelligent Braking" electronic regenerative, disc park brake
Battery ³	Standard: One 25.2V 18.2 Ah Lithium-Ion battery Optional: One 25.2V 10.4 Ah Lithium-Ion travel battery
Battery Charger	2 amp, off-board
Freewheel Operational Force	Less than 60 N
Drive Control Operational Force	Less than 5 N
Maximum Rated Slope	6° (10.5%)
Maximum Obstacle Climbing Ability (Ascending and Descending)	1.5 in. (40 mm)
Measured Sound Level (A-weighted)	Less than 65 dB

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ Lithium-Ion type required. See "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

⁷ Unit configured with optional travel battery does not comply with AS/NZS 3695.2 and EN12184 standards.

NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 Series, AS/NZS 3695.2, and EN12184 standards. All specifications subject to change without notice.



